



CONTRACTOR'S FAVORITE SINCE 1962

EZ Stain[®] **PREMIUM** Zero VOC

- **Highly Pigmented**
- **100% Inert**
- **Non-Toxic**

PIGMENT-BASED BASE COAT

Prime & Prep Concrete Over Repairs

For Horizontal & Vertical Surfaces



Before



After

Provides an Opaque Surface Before Applying Stain

- For concrete patios, driveways, walkways, artificial rocks, water features & more
- Conceals "bleed" rust from structural steel and rebar
- Cover up and blend concrete repairs that don't match
- Can be custom tinted with any Glaze 'N Seal EZ Stain color
- Use full strength or dilute to suit your application
- Reduces surface temperature in sunlight

1-800-486-1414

www.glaze-n-seal.com





PIGMENT-BASED BASE COAT

Prime & Prep Concrete Over Repairs

Provides an Opaque Surface Before Applying Stain

Glaze 'N Seal's EZ Stain Base Coat is simply the EASIEST way to prime & prep concrete before applying stain. Highly opaque and slightly off-white, it will conceal, cover up and blend imperfections and repairs that don't match creating a uniform surface. Our UV-stable formula uses rich pigments and nano-bonding technology for unmatched bonding that won't peel or flake.

Product Uses: Use INDOOR and OUTDOOR on any vertical or horizontal concrete surface or overlay. Ideal over repairs to concrete including patios, driveways, walkways and walls. Effectively covers rust stains outside of the repair area. Often used to prime entire concrete structures including artificial pool rocks and slides. Bonds permanently to all cementitious micro toppings & overlays, CMU block, pavers, etc.

Surface Prep: Clean surface completely. Remove oil, grease, gum, wax, foreign materials of any kind, including dust & dirt. Glaze 'N Seal's Heavy Duty Cleaner is recommended. For heavier stains like motor oil, use a heavy-duty degreaser. Efflorescence and mineral deposits can be removed with Glaze 'N Seal's Efflorescence Remover. New concrete should be at least 28 days old before application. Repairs should be given 36 hours cure time before application.

IF SURFACE IS NOT STRUCTURALLY SOLID, IT MUST BE REPAIRED OR REPLACED PRIOR TO APPLICATION

Application: EZ Stain Base Coat is ready-to-use, it can also be tinted with any Glaze 'N Seal EZ Stain color to assist in matching existing color of concrete. Dilute with water when "feathering" or "blending" repairs. Always test first on an inconspicuous area to ensure you get the desired appearance. To achieve high opacity, apply in coats. Use of a pump sprayer is the most common method to apply. Cone tips, sprayed in a circular motion, work better than fan tips. Pour through a paint filter to avoid clogs. Airless sprayers or HVLP guns may also be used. Agitate during application. Surface temperature should be between 50-100 degrees. When hot, apply early in the day. You may mist surface slightly with water to cool surface. Do not apply if rain is expected within 24 hrs.

SHAKE WELL BEFORE USE & FREQUENTLY DURING APPLICATION.

Clean Up: Wash with soap and water.

Coverage: One gallon will cover approximately 200-400 sq.ft. depending on the condition & porosity of the concrete. Dilute to create light color washes & increase coverage up to 600-700 sq.ft.

Dry Time: When Base Coat looks "FLAT", it has dried & additional coats of Base Coat can be applied if necessary or you may begin coloring with a Glaze 'N Seal EZ Stain color.

FOR PROFESSIONAL USE ONLY.

WARRANTY: Glaze 'N Seal product liability, either expressed or implied is limited solely to the replacement of this product when proven to be defective & does not include any labor costs or consequential damages. It is the user's responsibility to determine the safety, toxicity & suitability of this product.

SAFETY INFORMATION: CAUTION, Always wear eye protection & gloves. Use an OSHA/NOSH approved respirator when spraying indoors. Liquid contact with eyes & skin causes irritation. Do not ingest. Wash hands thoroughly after use. **FIRST AID:** Should eye contact occur, flush with plenty of water for 15 minutes. If irritation persists, get medical attention. For skin contact, flush skin with plenty of soap and water. If irritation persists, get medical attention. Refer to SDS for handling instructions.

WARNING

Contains Acrylic Polymers – Harmful if swallowed.

Do NOT induce vomiting – call a physician.

KEEP OUT OF REACH OF CHILDREN

This product does not meet the definition of a hazardous substance or preparation as defined by 29 CFR 1920.1200 or the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent directives.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • 800/486-1414
www.glaze-n-seal.com