



CONTRACTOR'S FAVORITE SINCE 1962

# EZ Stain<sup>®</sup> PREMIUM Zero VOC



## PIGMENT-BASED CONCRETE STAIN

Extreme Durability - Fade Resistant

Outperforms Dyes Beautiful Natural Look

- Advanced Nano-Bond Technology
- Superior Dye-Free Formula
- Easy Horizontal & Vertical Application
- Ideal for Multi-Colored Looks



Scan Here  
for  
Application  
Ideas  
and  
More Info



## The EASIEST Stain Ever

www.glaze-n-seal.com

1-800-486-1414



# PIGMENT-BASED CONCRETE STAIN

**Extreme Durability - Fade Resistant**

**Outperforms Dyes    Beautiful Natural Look**

Glaze 'N Seal's EZ Stain is simply the EASIEST, most versatile stain you can buy. Get the results you want – ready-to-use for a natural transparent look; dilute with water for a modern, washed look; add coats for deeper opacity; or mix with other EZ Stain colors for a custom look. Easier and less costly to maintain, our semi-transparent, UV-stable formula uses rich pigments and nano-bonding technology to provide exceptional fade resistance and unmatched bonding that won't peel or flake – outperforming commonly used dye-based stains.

**Product Uses:** Use INDOOR & OUTDOOR on any new or existing concrete surface or overlay. Ideal for recoloring faded integrally colored or stamped colored concrete. Easy to use on horizontal and vertical surfaces. It can also be used on wood & other porous non-sealed substrates.

**Surface Prep:** Clean surface completely. Remove oil, grease, gum, wax, foreign materials of any kind, including dust and dirt. Glaze 'N Seal's Heavy Duty Cleaner is recommended. For heavier stains like motor oil, use a heavy-duty degreaser. Efflorescence and mineral deposits can be removed with Glaze 'N Seal's Efflorescence Remover. New concrete should be at least 28 days old before staining and sealing.

**IF SURFACE IS NOT STRUCTURALLY SOLID, IT MUST BE REPAIRED OR REPLACED PRIOR TO STAINING.**

**Application:** EZ Stain is ready-to-use. Always test first on an inconspicuous area to insure you get the desired appearance and color. Only mix with other EZ Stain colors. Use of a pump sprayer is the most common method to apply stain. Cone tips, sprayed in a circular motion, work better than fan tips. Pour through a paint filter to avoid clogs. Airless sprayers or HVLP guns may also be used. Agitate during application. For faux looks dab with a sponge or brush. Surface temperature should be between 50-100 degrees. When hot, apply early in the day. You may mist surface slightly with water to cool surface. Do not apply if rain is expected within 24 hrs.

When repairing areas that are worn, badly stained, porous and/or rust stained, we recommend using EZ Stain Base Coat as a primer over repair before applying EZ Stain for a more uniform result.

**SHAKE WELL BEFORE USE & FREQUENTLY DURING APPLICATION.**

**Clean Up:** Wash with soap and water.

**Coverage:** One gallon ready-to-use will cover approximately 200-400 sq.ft. depending on the condition and porosity of the concrete. If diluted to create light color washes, coverage may increase to 600-700 sq.ft.

**Dry Time:** When color looks "FLAT", stain has dried & additional colors can be applied. Allow 1-3 hours additional "CURE" time after final stain coat. For best results, always apply two or more coats of a film forming "pro grade" sealer like Glaze 'N Seal's Multi-Purpose Sealer or Wet Look Lacquer. This will protect the stain. Apply only when surface temperature is between 50-90 degrees. Do not apply if rain is expected within the next 24 hours. Turn off garden sprinklers.

**FOR PROFESSIONAL USE ONLY.**

**WARRANTY:** Glaze 'N Seal product liability, either expressed or implied is limited solely to the replacement of this product when proven to be defective & does not include any labor costs or consequential damages. It is the user's responsibility to determine the safety, toxicity & suitability of this product.

**SAFETY INFORMATION:** CAUTION, Always wear eye protection & gloves. Use an OSHA/NOSH approved respirator when spraying indoors. Liquid contact with eyes & skin causes irritation. Do not ingest. Wash hands thoroughly after use. FIRST AID: Should eye contact occur, flush with plenty of water for 15 minutes. If irritation persists, get medical attention. For skin contact, flush skin with plenty of soap and water. If irritation persists, get medical attention. Refer to SDS for handling instructions.

## WARNING

Contains Acrylic Polymers – Harmful if swallowed.  
Do NOT induce vomiting – call a physician.  
**KEEP OUT OF REACH OF CHILDREN**

This product does not meet the definition of a hazardous substance or preparation as defined by 29 CFR 1920.1200 or the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent directives.



**Quality Products for Concrete, Tile and Masonry**

Glaze 'N Seal Products, Irvine, CA • 800/486-1414  
www.glaze-n-seal.com